



Burke Wall Base

Mannington
COMMERCIAL



Cover: BurkeBase® - 204 Gray (ACCORD color), **Confluence Modular Carpet** - Optimism 81010, Security 63014 (Installation - Vertical Ashlar)
Above: BurkeBase® - 820 Daffodil (ACCORD color), **Abstracted Strie LVT** - Core ANT400

Performance and Features

Available Heights/Sizes	BurkeBase® Premium TS Molded 1/8" *	BurkeBase® Type TP 1/8" **	BurkeBase® Type TV 1/8" **	BurkeBase® Type TV .080" **
	4" (102 mm)	2.5" (64 mm)	2.5" (64 mm)	2.5" (64 mm)
	6" (152 mm)	4" (102 mm)	4" (102 mm)	4" (102 mm)
		4.5" (114 mm)	4.5" (114 mm)	6" (152 mm)
		6" (152 mm)	6" (152 mm)	
	Coved	Coved or Toeless	Coved or Toeless	Coved or Toeless

Warranty This product is backed by our Limited 5-Year Commercial Warranty.

Corners BurkeBase® Premium TS Molded factory molded corners are available 4" and 6" coved corners. Must be ordered at time of wall base order to ensure color match.

BurkeBase® Type TP/TV pre-formed corners are available in all profile sizes. Must be ordered at time of wall base order to ensure color match.

Custom Colors Minimums apply.

Please make final selection for all colors from actual product samples.

For samples and information visit manningtoncommercial.com or call 800.241.2262.



BurkeBase® - Pecan 504 (ACCORD color), **English Walnut** - Kelen 5684R

Thermoset Rubber

BurkeBase® Premium TS Molded Wall Base Benefits

- Vulcanized thermoset rubber to prevent shrinkage or expansion
- Molded to provide dimensional stability
- Smooth satin finish and inherent flexibility helps hide substrate irregularities
- Available in 4' lengths
- 25 standard colors

Thermoplastic Rubber

BurkeBase® Rubber Wall Base Type TP Benefits

- Heavy gauge rubber base
- Flexible formulation easily forms to curves and corners for clean installation
- Will not fade or crack
- Scuff and scratch resistant
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors

Vinyl

BurkeBase® Vinyl Wall Base Type TV Benefits

- Engineered for heavy traffic and high maintenance areas
- Scuff and abrasion resistant
- Tough matte finish helps hide substrate irregularities
- Available in .080" and .125" gauges
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors

BurkeBase®

Style	BurkeBase Premium TS Molded Wall Base 1/8" *	BurkeBase Type TP 1/8" ** (Non-Ortho Phthalate)
Construction	Thermoset Rubber	Thermoplastic Rubber
Finish	Satin	Matte
Classification	ASTM F1861 Type TS, Group 1	ASTM F1861 Type TP, Group 1
Total Thickness	1/8" (3.2 mm)	1/8" (3.2 mm)
Profile	Coved 4" (102 mm) 6" (152 mm)	Coved or Toeless 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)
Colors	25	100 (36 are Accord)
Packaging	25-4' pieces = 100' per carton	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10"	Coved = 27/39/53 lbs.	Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs.
Weight Per Carton – Corners	Coved = 3/4/7 lbs.	Coved = 3/4/9 lbs. Coved = 3/4/9 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory molded corners available	Factory pre-formed corners available
Adhesive	MR-101	MR-101
Testing		
Static Load (ASTM E970)	500 psi	
Flooring Radiant Panel (ASTM E648)	Passes - Class I; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - < 450	
Environmental Data		
Indoor Air Quality	FloorScore Certified	
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials	
Manufacturing	Calhoun, GA and Eustis, FL (USA)	
Warranty		
	Limited 5-Year Commercial Warranty	

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved 4' lengths available in 4" and 6".

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights.

BurkeBase®

Style	BurkeBase Type TV 1/8" ** (Non-Ortho Phthalate)	BurkeBase Type TV .080" ** (Non-Ortho Phthalate)
Construction	Vinyl	Vinyl
Finish	Matte	Matte
Classification	ASTM F1861 Type TV, Group 1	ASTM F1861 Type TV, Group 1
Total Thickness	1/8" (3.2 mm)	.080" (2.0 mm) & 1/8" (3.2 mm)
Profile	Coved or Toeless	Coved or Toeless
Sizes	2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)	2.5" (64 mm) 4" (102 mm) 6" (152 mm)
Colors	100	100
Packaging	1-100' continuous roll or 25-4' pieces	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10"	Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs.	Coved (.080") = 19/27/41/42 lbs. Toeless (.080") = 17/25/41/39 lbs.
Weight Per Carton – Corners	Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs.	Coved (.080") = 3/3/8 lbs. Toeless (.080") = 2/3/7 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory pre-formed corners available	Factory pre-formed corners available
Adhesive	MR-101	MR-101
Testing		
Static Load (ASTM E970)	500 psi	
Flooring Radiant Panel (ASTM E648)	Passes - Class I; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - < 450	
Environmental Data		
Indoor Air Quality	FloorScore Certified	
Product Declarations	HPD	
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials	
Manufacturing	Calhoun, GA and Eustis, FL (USA)	
Warranty		
	Limited 5-Year Commercial Warranty	

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved 4" lengths available in 4" and 6".

** Type TP & TV Coved and Toeless 4" lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights.