

Style	Groove, Stride
Construction	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)
Wear Layer	Quantum Guard Elite®
Edge Treatment	Micro-bevel
Sizes	6" x 36" (152 mm x 915 mm) 12" x 24" (305 mm x 610 mm) 18" x 18" (457 mm x 457 mm)
Colors	20 each style
Packaging	6" x 36" - 19 pcs, 28.5 ft <sup>2</sup> (2.648 m <sup>2</sup> ), 21.23 lbs (9.63 kg) 12" x 24" - 18 pcs, 36 ft <sup>2</sup> (3.345 m <sup>2</sup> ), 26.82 lbs (12.17 kg) 18" x 18" - 12 pcs, 27 ft <sup>2</sup> (2.508 m <sup>2</sup> ), 20.12 lbs (9.126 kg) Packaging may differ for QuickStix®
Adhesive	<b>Porous &amp; Non-porous Substrates:</b> V-95 Full Spread 2-part Epoxy V-88 Full Spread, Transitional Pressure Sensitive, High Moisture XpressStep for LVT & Sheet Vinyl Full Coverage Spray XpressStep Premium for LVT Full Coverage High Moisture Spray <b>Porous Substrates Only:</b> V-82 Full Spread <small>Note: Must use V-95, XpressStep or XpressStep Premium under hospital beds and heavy rolling load areas. Use V-95 in Operating Rooms or where higher risk of topical moisture would be a concern.</small>
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.
<b>Testing</b>	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft.
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
<b>Environmental Data</b>	
Rapidly Renewable Content	Contains 2% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered
<b>Warranty</b>	
	Limited 15 Year Commercial Warranty Limited 15 Year Quantum Guard Elite® Wear Warranty