

Style	ColorFields Tile	ColorFields Sheet
Construction	Thermoset Rubber Floor Tile	Thermoset Rubber Sheet Flooring without Backing
Classification	ASTM F1344 Class 1, Grade 1, Type B	ASTM F1859, Type 1
Total Thickness	0.118" (3 mm)	0.118" (3 mm)
Profile	Smooth	Smooth
Sizes	24" x 24" (610 x 610 mm)	4' x 49.2' (1.2 x 15 m) Sheet (Full rolls only)
Colors	21	21
Packaging	20 pcs, 80 ft ² (7.432 m ²), 78 lbs (35.38 kg)	196.85 ft ² (18.28 m ²)/roll, 191.49 lbs (86.86 kg)/roll
Adhesive	MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive MR-911 Acrylic Adhesive	MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive MR-911 Acrylic Adhesive
Seam Method	N/A	Mannington Commercial Weld Rods
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%	
Squareness (ASTM F540)	Passes - 0.010" Max (Tile)	
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85	
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"	
Static Load (ASTM E970 mod.)	Passes - 1,200 PSI; Residual Indent ≤ 0.005"	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Rapidly Renewable Content	Contains 6% rapidly renewable resource content	
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information	
Warranty		
	Limited 10 Year Commercial Warranty Limited 5 Year Wear Warranty	